

INFOCRANK 110 BCD 24mm	
Spider	Standard 110mm BCD five bolt
Spindle	24mm Shimano™ Standard
Crank	Drop forged 6000 series alloy 145mm Q-Factor 165mm, 170mm, 172.5mm, 175mm, 177.5mm and 180mm crank length
Pedal	Standard 9/16-inch pedal threads accept all major pedals
Chainring options	50/34 Compact Praxis 52/36 Mid-Compact Praxis 53/39 Verve TA Aero Chain ring set
Weight	Spider, spindle, crank arms: 700g

[NEXT PAGE FOR POWER METER SPECIFICATIONS >](#)

## INFOCRANK POWER METER SPECIFICATIONS

Environmental	Ingress protection level	IPX7, resists up to 1m immersion
	Operating humidity	0 - 100%
	Chemical resistance	Resists typical lubricants and bike cleaning chemicals
	Battery operating temperature	0 - 60° celsius
Mechanical	Certifications	Certified to market specific standards
	Maintenance	User serviceable parts: bottom brackets, chainrings, seals, batteries, and power module housing spares
System	Battery	User replaceable, SR44 (Silver Oxide) also 303 or 357
	Battery life	Over 500 hrs (operational)
	Start up time	< 2 secs (or as per bike computer display)
Data processing	Wireless communications	ANT+ protocol
	Wireless range	2m
	Power range	0 - 3000 Watts
	Cadence range	10 - 200 rpm

CONTINUED >

## INFOCRANK POWER METER SPECIFICATIONS

Accuracy	Cadence	±1 rpm
	Torque	±0.2 Nm accuracy for measurements below 20 Nm, and ±1% of actual readings for measurements above 20 Nm
	Power	± 0.37% error (99.63% accurate) for 20 - 100kg loads. Download Accuracy Certification <a href="#">here</a> .
Product	Warranty	2 years
	Software	Compatible with major data analytics: Training Peaks, Golden Cheetah, Cycling Analytics, VeloPro, Strava, Garmin Training Centre
	Firmware	Free updates available via our website
	Power meter metrics	Individual Left / Right Power Balance Total Power L/R Pedal Smoothness L/R Torque Effectiveness Cadence and more ANT+ metrics